



Centering Device
CE-9



CE-9 Specifications

Layout span	Horizontal: ± 15 mm (1 mm increments) Vertical: ± 10 mm (1 mm increments) Slide center blocking
Light source	White LED
Blocking method	Manual
Blocking accuracy	Position: $\phi 0.5$ mm or less Axis angle: $\pm 0.5^\circ$ or less
Power supply	AC 100 to 240 V, 50 / 60 Hz
Power consumption	22 VA
Dimensions / Mass	113 (W) x 155 (D) x 214 (H) mm / 1.7 kg 4.5 (W) x 6.3 (D) x 8.4 (H) " / 3.8 lbs.
Standard accessories	Power cord, Frame change holder, AC adapter

Key Features

- Maintenance-free LED light with improved cost efficiency
- Light control for optimum visibility
- Compact and stylish design



Specifications and design are subject to change without notice.



HEAD OFFICE
(International Div.)
34-14 Maehama,
Hiroishi-cho, Gamagori,
Aichi 443-0038, JAPAN
TEL: +81-533-67-8895
URL: www.nidek.com
[Manufacturer]

TOKYO OFFICE
(International Div.)
3F Sumitomo Fudosan Hongo
Bldg., 3-22-5 Hongo, Bunkyo-ku,
Tokyo 113-0033, JAPAN
TEL: +81-3-5844-2641
URL: www.nidek.com

NIDEK INC.
2040 Corporate Court,
San Jose, CA 95131, U.S.A.
TEL: +1-408-468-6400
+1-800-223-9044
(US Only)
URL: usa.nidek.com

NIDEK S.A.
Europarc,
13 rue Auguste Perret,
94042 Créteil, FRANCE
TEL: +33-1-49 80 97 97
URL: www.nidek.fr

NIDEK TECHNOLOGIES S.R.L.
Via dell'Artigianato,
6/A, 35020 Albignasego (Padova),
ITALY
TEL: +39 049 8629200/8626399
URL: www.nidektechnologies.it

NIDEK (SHANGHAI) CO., LTD.
Rm3205, Shanghai Multi
Media Park, No.1027 Chang
Ning Rd, Chang Ning District,
Shanghai, CHINA 200050
TEL: +86 021-5212-7942
URL: www.nidek-china.cn

NIDEK SINGAPORE PTE. LTD.
51 Changi Business Park
Central 2, #06-14,
The Signature 486066,
SINGAPORE
TEL: +65 6588 0389
URL: www.nidek.sg